

ZOLOTO[®] BRONZE VERTICAL CHECK VALVE (Screwed)



SALIENT FEATURES :

- Screwed Female ends to IS 554/ BS 21/ ISO 7.
- Single piece design. •

SUITABLE FOR

Steam

- Meant for Vertical lines alone.
- Permits flow in one direction and closes automatically if the flow reverses.
- Design standard IS 778, Class-1.


Water

• Can be provided with rubber 'O' ring seating also at no extra cost.

Oil

Name of Part	Material	Specification
Body	Bronze	IS 318 Gr. LTB 2
Disc	Bronze	IS 318 Gr. LTB 2
Nut	Brass	IS 319 Gr. 2
	and a second	(Half Hard)
Split Pin 💧	Phosphourous	IS 7608
	Bronze	
'O' Ring	Nitrile Rubber	IS 5192-1
and the second s		
Lat :		

SIZE:	: DIMENSION		
Inches	mm	А	
1/2	15	65	
3/4	20	70	
1	25	75	
11/4	32	85	
11/2	40	95	
2	50	110	
100			
-	199		
	in the		
-	-	State of the second	



Air

Gases

Test Pressure (Hydraulic) Shell : 1.5MPa Seat : 0.25MPa



1037







SALIENT FEATURES :

- Screwed Female ends to IS 554/ BS 21 / ISO 7.
- Screwed in bonnet, meant for Horizontal lines only.
- Permits flow in one direction and shuts
- automatically if the flow reverses. Metal disc is mushroom shaped with spherical seating surface.
- Disc is guided in body as well as in bonnet. 0
- Design standard IS 778, Class-1. 0
- Can be provided with rubber 'O' ring seating also . at no extra cost.


SUITABLE FOR



MATERIALS :

Name of Part	Material	Specification	
Body	Bronze	IS 318 Gr. LTB 2	
Bonnet	Bronze/	IS 318 Gr. LTB 2/	
	Forged Brass	IS 6912 Gr. FLB	
Disç	Bronze	IS 318 Gr. LTB 2	
'O' Ring	Nitrile Rubber	IS 5192-1	
	Sa Contractor		
Station of		1	
142 S. S. S.			
18 - S.			

SIZE: DIMEN			ENSION	۹S:
Inches	mm	А	B	
1/2	15	60	40	
3/4	20	70	45	
1	25	80	55	
11/4	32	95	59	
11/2	40	110	65	
2	50	125	74	24
21/2	65	160	85	
3	80	180	105	1
4	100	216	131	-



Test Pressure (Hydraulic) Shell : 1.5MPa Seat : 0.25MPa

23